

```

#!/bin/sh
### ===== ###
##          ##
## ReadyAPI TestCaseRunner Bootstrap Script      ##
##          ##
### ===== ###

### $Id$ ###

DIRNAME=`dirname $0`

# OS specific support (must be 'true' or 'false').
cygwin=false;
case "`uname`" in
  CYGWIN*)
    cygwin=true
    ;;
esac

# Setup READY_API_HOME
# get the full path (without any relative bits)
READY_API_HOME=`cd $DIRNAME/..; pwd`

export READY_API_HOME

if [ -f "$READY_API_HOME/jre/bin/java" ]
then
  JAVA=$READY_API_HOME/jre/bin/java
else
  if [ -f "$READY_API_HOME/../../Plugins/jre.bundle/Contents/Home/bin/java" ]
  then
    JAVA=$READY_API_HOME/../../Plugins/jre.bundle/Contents/Home/bin/java
  else
    if [ -f "$JAVA_HOME/bin/java" ]
    then
      JAVA=$JAVA_HOME/bin/java
    else
      JAVA=java
    fi
  fi
fi

READY_API_CLASSPATH=$READY_API_HOME/bin/ready-api-ui-3.2.5.jar:$READY_API_HOME/lib/*
JFXRTPATH=`$JAVA -cp $READY_API_CLASSPATH com.eviware.soapui.tools.JfxrtLocator`
READY_XMX=`$JAVA -cp $READY_API_CLASSPATH com.eviware.soapui.tools.XmxCalculator`
#uncomment to override memory limit
#READY_XMX=4000m
READY_API_CLASSPATH=$JFXRTPATH$READY_API_CLASSPATH

export READY_API_CLASSPATH

```

```
JAVA_OPTS="-Xms128m -Xmx$READY_XMX -Dtest.history.disabled=true -
Dsoapui.properties=soapui.properties -Dgroovy.source.encoding=iso-8859-1 -
Dsoapui.home=$READY_API_HOME/bin"
```

```
#JAVA 12
```

```
JAVA_OPTS="$JAVA_OPTS --add-opens java.base/java.lang=ALL-UNNAMED --add-opens
java.base/java.lang.invoke=ALL-UNNAMED --add-opens java.desktop/java.beans=ALL-UNNAMED --
add-opens java.base/java.util=ALL-UNNAMED --add-opens java.base/java.lang.reflect=ALL-
UNNAMED --add-opens java.base/java.util.concurrent.atomic=ALL-UNNAMED --add-opens
java.xml/com.sun.org.apache.xerces.internal.util=ALL-UNNAMED"
```

```
if [ $READY_API_HOME != "" ]
```

```
then
```

```
    JAVA_OPTS="$JAVA_OPTS -Dsoapui.ext.libraries=$READY_API_HOME/bin/ext"
```

```
    JAVA_OPTS="$JAVA_OPTS -Dsoapui.ext.listeners=$READY_API_HOME/bin/listeners"
```

```
    JAVA_OPTS="$JAVA_OPTS -Dsoapui.ext.actions=$READY_API_HOME/bin/actions"
```

```
fi
```

```
export JAVA_OPTS
```

```
# For Cygwin, switch paths to Windows format before running java
```

```
if $cygwin
```

```
then
```

```
    READY_API_HOME=`cygpath --path --dos "$READY_API_HOME"`
```

```
    READY_API_CLASSPATH=`cygpath --path --dos "$READY_API_CLASSPATH"`
```

```
fi
```

```
echo =====
```

```
echo =
```

```
echo = READY_API_HOME = $READY_API_HOME
```

```
echo =
```

```
echo =====
```

```
$JAVA $JAVA_OPTS -cp $READY_API_CLASSPATH
```

```
com.smartbear.ready.cmd.runner.pro.SoapUIProTestCaseRunner "$@"
```